

Application No. 10/608,995

Filed: June 27, 2003

TC Art Unit: 3679

Confirmation No.: 6412

THE CLAIMS

1. (Currently Amended) An assembly system for a pipe coupling, said system comprising:

a first pipe element and a second pipe element, the pipe elements each having an outwardly directed circumferential bead or flange,

a circumferential clamping device to be applied on the outside of the ends of said pipe elements and to be tightened around the same when said two pipe elements are placed end-to-end, and

a coupling device disposed between said ends of said first and said second pipe elements and beneath said circumferential clamping device, and configured to align and/or hold said two pipe elements during the assembly, said coupling device having at least one coupling means extending outwardly in an axial direction towards said pipe elements, and said coupling means configured to engage said beads or flanges of said two pipe elements on the outside of the pipe elements.

2. (Cancelled)

3. (Cancelled)

4. (Previously Presented) The system as claimed in claim 1, wherein each outwardly directed circumferential bead or flange is disposed at the end of the pipe element.

Application No. 10/608,995

Filed: June 27, 2003

TC Art Unit: 3679

Confirmation No.: 6412

5. (Currently Amended) The system as claimed in claim 4, wherein said coupling device is a ring comprising a first and a second coupling means, where said first coupling means is adapted to outwardly engage said ~~first pipe element or said bead or flange~~ of said first pipe element and said second coupling means is adapted to outwardly engage and/or hold said ~~second pipe element or said bead or flange~~ of said second pipe element.

6. (Original) The system as claimed in claim 5, wherein said coupling means has a groove adapted to engage said beads or flanges of said pipe elements.

7. (Original) The system as claimed in claim 5, wherein said coupling means is adapted to engage a part of said pipe elements or a part of said beads or flanges of said pipe elements.

8. (Original) The system as claimed in claim 5, wherein said first coupling means extends along part of the circumference of said ring so as to engage said first pipe element or said bead or flange of said first pipe element, and said second coupling means extends along part of the circumference of said ring so as to engage and/or hold said second pipe element or said bead or flange of said second pipe element.

9. (Currently Amended) The system as claimed in claim 5, wherein said first coupling means is adapted to outwardly engage an upper part of said first pipe element or said bead or flange of said first pipe element and said second coupling means is adapted

Application No. 10/608,995

Filed: June 27, 2003

TC Art Unit: 3679

Confirmation No.: 6412

to outwardly engage ~~and/or~~ or hold a lower part of said second pipe element or said bead or flange of said second pipe element.

10. (Original) The system as claimed in claim 5, wherein said coupling ring comprises a plurality of said first coupling means and a plurality of said second coupling means, said first and second coupling means being spaced apart along the circumference of said coupling ring.

11. (Original) The system as claimed in claim 5, wherein said coupling means comprises friction enhancing means on the surface facing said pipe elements or said bead or flange of said pipe elements.

12. (Original) The system as claimed in claim 1, wherein the coupling device comprises sealing means.

13. (Original) The system as claimed in claim 1, wherein said coupling device is made of plastic material, rubber material, metal or reinforced fibre material.

14. (Original) The system as claimed in claim 4, wherein said clamping device is tightened around said ends of said pipe elements or said beads or flanges of said pipe elements and said coupling device by a locking mechanism.

15. (Previously Presented) The system as claimed in claim 1, wherein the coupling device is an integrated part of said end of said first pipe element.

Application No. 10/608,995

Filed: June 27, 2003

TC Art Unit: 3679

Confirmation No.: 6412

16. (Currently Amended) A method for coupling a first pipe element and a second pipe element, the pipe elements each having an outwardly directed circumferential bead or flange, said method comprising

- applying a circumferential clamping device on the outside of said first pipe element in an untightened position;
- arranging a coupling device in engagement with ~~the end~~ said bead or flange of said first pipe element;
- bringing ~~the end~~ said bead or flange of said second pipe element into engagement with said coupling device, thus aligning ~~and/or~~ or holding said two pipe elements during the assembly;
- applying said circumferential clamping device on the outside of said ends of said pipe elements; and
- tightening said circumferential clamping device around said ends of said pipe elements.

17. (Currently Amended) A method for coupling a first pipe element and a second pipe element, the pipe elements each having an outwardly directed circumferential bead or flange, use being made of an assembly system comprising a circumferential clamping device, which is applied on the outside of the ends of said pipe elements and tightened around the same when said two pipe elements are placed end-to-end, wherein a coupling device is arranged between said ends of said first and second pipe elements and in engagement with the bead or flange of the two pipe elements on the outside of the two pipe elements, to align

Application No. 10/608,995

Filed: June 27, 2003

TC Art Unit: 3679

Confirmation No.: 6412

and/or or hold said two pipe elements during the assembly, and  
tightening the clamping device to couple the two pipe elements  
together.

18. (Previously Presented) Use of an assembly system as claimed in claim 1 for coupling a first pipe element and a second pipe element.

19. (Previously Presented) The use of the assembly system as claimed in claim 18, wherein each outwardly directed circumferential bead or flange is disposed at the end of the pipe element.

20. (Currently Amended) A coupling device for an assembly system for a pipe coupling including a first pipe element and a second pipe element, the pipe elements each having an outwardly directed circumferential bead or flange, said coupling device configured to be disposed between ends of said first and said second pipe elements, said coupling device having at least one coupling means extending outwardly in the axial direction, said coupling means configured to engage said beads or flanges of said two pipe elements on their outside.

21. (Currently Amended) The coupling device as claimed in claim 20, wherein said coupling device is a ring comprising a first and a second coupling means, where said first coupling means is adapted to outwardly engage said first pipe element and said second coupling means is adapted to outwardly engage and/or or hold said second pipe element.

Application No. 10/608,995

Filed: June 27, 2003

TC Art Unit: 3679

Confirmation No.: 6412

22. (Original) The coupling device as claimed in claim 21, wherein said first coupling means is adapted to outwardly engage an upper part of said first pipe element and said second coupling means is adapted to outwardly engage and/or hold a lower part of said second pipe element.

23. (Original) The coupling device as claimed in claim 21, comprising two semi-circular coupling means.

24. - 25. (Cancelled)

26. (Currently Amended) ~~The~~ An assembly system as claimed in claim 4, for a pipe coupling, said system comprising:

a first pipe element, a second pipe element, and a circumferential clamping device to be applied on the outside of the ends of the pipe elements and to be tightened around the pipe elements when the two pipe elements are placed end-to-end;

a coupling device to be arranged between the ends of the first and the second pipe elements and beneath the circumferential clamping device, wherein the coupling device has at least one coupling means extending outwardly in an axial direction towards the pipe elements and wherein the second pipe element has an outwardly directed circumferential bead or flange;

wherein the coupling device is an integrated part of said end of said first pipe element and the coupling means is arranged to engage the bead or flange of the second pipe element on its outside so as to align or hold the two pipe elements during the assembly.

Application No. 10/608,995  
Filed: June 27, 2003  
TC Art Unit: 3679  
Confirmation No.: 6412

27. - 38. (Cancelled)

39. (Previously Presented) Use of an assembly system as claimed in claim 4 for coupling a first pipe element and a second pipe element.

40. (Previously Presented) Use of an assembly system as claimed in claim 5 for coupling a first pipe element and a second pipe element.

41. (Previously Presented) Use of an assembly system as claimed in claim 6 for coupling a first pipe element and a second pipe element.

42. (Previously Presented) Use of an assembly system as claimed in claim 7 for coupling a first pipe element and a second pipe element.

43. (Previously Presented) Use of an assembly system as claimed in claim 8 for coupling a first pipe element and a second pipe element.

44. (Previously Presented) Use of an assembly system as claimed in claim 9 for coupling a first pipe element and a second pipe element.

Application No. 10/608,995

Filed: June 27, 2003

TC Art Unit: 3679

Confirmation No.: 6412

45. (Previously Presented) Use of an assembly system as claimed in claim 10 for coupling a first pipe element and a second pipe element.

46. (Previously Presented) Use of an assembly system as claimed in claim 11 for coupling a first pipe element and a second pipe element.

47. (Previously Presented) Use of an assembly system as claimed in claim 12 for coupling a first pipe element and a second pipe element.

48. (Previously Presented) Use of an assembly system as claimed in claim 13 for coupling a first pipe element and a second pipe element.

49. (Previously Presented) Use of an assembly system as claimed in claim 14 for coupling a first pipe element and a second pipe element.

50. (Previously Presented) Use of an assembly system as claimed in claim 15 for coupling a first pipe element and a second pipe element.



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**